



Multi-purpose full asymmetric and symmetric lift that is height and width adjustable and may be installed in a standard or rotated column configuration to accommodate the smallest cars to the largest SUV's and trucks.

Features:



- **ALI Certified**
- **Adjustable column height** – Provides an extra 6" of height adjustment for ease of installation with various ceiling heights
- **Adjustable column width** – Provides an extra 6" of width adjustment for narrow service bays to custom fit your shop
- **Rubber door guards** – Provides added security against door damage
- **Outer hose guards** – protects hydraulic hoses from damage
- **Single point lock release** – allows technicians to disengage both column locks simultaneously
- **Heavy-duty arm restrain system** – oversize rugged steel gears, pins and springs for trouble free operation
- **3-stage front arm design** enables you to position doors in front of the column or behind to avoid door damage.
- **Double telescoping screw pads** – used with or without rubber pads offering 6.5" adjustment for complete vehicle coverage
- Lift Extensions included – 4-6" & 4-3"
- Fastening hardware included



Specifications	TPO310AS
Lifting Height	76.4"
Column Height	142.9 -148.8"
Cylinder Full Height	145.2"
Total width	130.7" – 136.6"
Drive Thru Clearance	98.4"
Floor to Overhead Switch	139.1" - 145"
Front Arm Reach(min/max)	23.6"/43.5"
Rear Arm Reach(min/max)	38.6"/61.8"
Screw Pad Height	4" to 7.5"
Inside Column Width	104.2" – 110"
Voltage	208-230V 1Ph
Rise Speed	54 Sec.

