



Note: Product may vary slightly from image shown.





PRECISION BALANCING

Engineered for motorcycle repair facilities demanding maximum accuracy and speed. Features a rapid 10-second balancing time to ensure maximum shop throughput.

IDEAL FOR:

- ✓ Independent Motorcycle Shops
- ✓ Dealership Service Centers
- ✓ Powersports Garages

SYSTEM FEATURES

-  **1" - 25" Rim Diameter**
Versatile clamping range for a wide variety of motorcycle wheels.
-  **110 lbs Max Wheel Weight**
Heavy-duty shaft handles large cruiser and touring wheels with ease.
-  **31" Max Wheel Diameter**
Accommodates oversized custom and off-road motorcycle tires.
-  **10-Second Balancing Time**
Rapid spin cycle increases productivity and reduces customer wait times.

- Max Rim Width - 7.5"
- Power Supply - 100/230V
- Machine Net Weight - 237 lbs
- Digital Display Interface

DISTRIBUTOR PROGRAM

We are looking for distributors and installers in Canada and the USA. Contact us for details.

SPECIFICATIONS

BL-630M | MOTORCYCLE WHEEL BALANCER

POWER REQUIREMENTS

100/230V

MACHINE CAPACITY

Max Wheel Weight: 110 lbs

Max Wheel Diameter: 31"

Max Rim Width: 7.5"

SHIPPING & WEIGHT

Shipping Dimensions: 42" x 22" x 46"

Shipping Weight: 350 lbs

Machine Net Weight: 237 lbs

SPACE REQUIREMENTS

40" x 50" x 14.5"

Ensure adequate clearance around the machine for safe loading and unloading of motorcycle wheels.

TECHNICAL CLEARANCES & EQUIPMENT PROFILE

Height: 40"



Depth: 14.5"

Width: 50"

DIMENSIONS, COLOURS AND ITEMS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE DUE TO OUR CONTINUOUS IMPROVEMENT PROGRAM.

Daytona

101 Applewood Dr, Brighton, ON K0K1H0

☎ 1-866-219-9991 / 613-475-5400

✉ customercare@daytonaproducts.com

🌐 www.daytonaproducts.com