



Note: Product may vary slightly from image shown.

PROFESSIONAL PERFORMANCE

A tilting column pneumatic tire changer designed for high-volume shops. Engineered to handle stiff, wide, and low-profile tires without compromising rim integrity.

- ✓ Performance Shops
- ✓ Tire Centers
- ✓ Car Dealerships
- ✓ Repair Garages

SYSTEM FEATURES

- ↑ Tilting Column System**
Pneumatic tilting column and locking system for faster setup and increased rigidity.
- 🛡 Rim Protection**
Includes rim clamp protectors and dismount head protectors for delicate chrome/alloy rims.
- 🌀 Bead Seating Air Blaster**
Oversized air blaster integrated into the jaws for immediate bead seating on stubborn tires.
- ✂ Pneumatic Bead Breaker**
Powerful 2.75-ton bead breaker system ensures efficient separation of tire and rim.
- ⚡ Full Air Preparation**
Factory-installed lubricator, filter, water trap, and regulator for long-term reliability.

Looking for **DISTRIBUTORS & INSTALLERS**

Available across Canada and the USA. Contact us for exclusive details.

SPECIFICATIONS

TC-890T | HEAVY DUTY TILTING COLUMN



CLAMPING & CAPACITY

| | |
|-------------------|-----------|
| Inside Clamping | 15" - 28" |
| Outside Clamping | 13" - 26" |
| Max Tire Diameter | 42" |
| Max Wheel Width | 14" |

POWER & AIR

| | |
|--------------------|------------------|
| Motor Power | 1.5 HP |
| Electrical | 120V / 20A / 1Ph |
| Air Requirement | 120 - 145 PSI |
| Bead Breaker Force | 2500 kg |

OPERATIONAL FOOTPRINT

66"W x 69"D x 79"H

Dimensions include full range of motion for tilting column and swing arm.

SHIPPING DATA

| | |
|-------------------|---------|
| Body Weight | 700 lbs |
| Arm Weight | 250 lbs |
| Total Ship Weight | 950 lbs |

EQUIPMENT PROFILE & CLEARANCES



Height: 79"

Width: 66"

CONTINUOUS IMPROVEMENT MAY RESULT IN SPECIFICATION CHANGES WITHOUT NOTICE.

